



**CERT**

# DVGW type examination certificate

## DVGW-Baumusterprüfzertifikat

**DW-6340BN3863**

Registration Number  
Registriernummer

<b>Field of Application</b> <i>Anwendungsbereich</i>	products of water supply <i>Produkte der Wasserversorgung</i>
<b>Owner of Certificate</b> <i>Zertifikatinhaber</i>	Samson AG Weismüllerstraße 3, D-60314 Frankfurt am Main
<b>Distributor</b> <i>Vertreiber</i>	Samson AG Weismüllerstraße 3, D-60314 Frankfurt am Main
<b>Product Category</b> <i>Produktart</i>	valves for drinking water: motor operated control valve (6341)
<b>Product Description</b> <i>Produktbezeichnung</i>	three-way valve (electrically respectively pneumatically controlled) as mixing or flow-diverting valve
<b>Model</b> <i>Modell</i>	Typ 3226
<b>Test Reports</b> <i>Prüfberichte</i>	laboratory control test: from 07.03.2022 (TZW) type testing: TA 020/14 from 30.03.2015 (TZW) type testing: TA 037/11 from 09.01.2012 (TZW) UBA-Guideline: K-340122-21-Kr/sg from 15.02.2021 (WHY)
<b>Test Basis</b> <i>Prüfgrundlagen</i>	DVGW 31-24/2-2007 (31.10.2002) UBA BWGL-Metalle (14.05.2020) UBA Übergangsregelung KTW-BWGL (10.07.2020) DVGW W 270 (01.11.2007)
<b>Date of Expiry / File No.</b> <i>Ablaufdatum / Aktenzeichen</i>	20.12.2027 / 22-0460-WNV

70228-01-A-0E

28.09.2022 LE A-1/2

Date, Issued by, Sheet, Head of Certification Body  
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle



Deutsche  
Akkreditierungsstelle  
D-ZE-16028-01-05

DVGW CERT GmbH  
Zertifizierungsstelle

Josef-Wirmer-Str. 1-3  
53123 Bonn

Tel. +49 228 91 88 - 888  
Fax +49 228 91 88 - 993

www.dvgw-cert.com  
info@dvgw-cert.com

<b>Type</b> <i>Typ</i>	<b>Technical Data</b> <i>Technische Daten</i>	<b>Remarks</b> <i>Bemerkungen</i>
Typ 3226	pressure rating: PN 10 nominal diameter: DN 15	
Typ 3226	pressure rating: PN 10 nominal diameter: DN 20	
Typ 3226	pressure rating: PN 10 nominal diameter: DN 25	
Typ 3226	pressure rating: PN 10 nominal diameter: DN 32	
Typ 3226	pressure rating: PN 10 nominal diameter: DN 40	
Typ 3226	pressure rating: PN 10 nominal diameter: DN 50	

<b>Type Variation</b> <i>Ausführungsvariante</i>	<b>Explanations</b> <i>Erläuterungen</i>
Mischventil	2 inlets; 1 outlet
Verteilventil	1 inlet; 2 outlets