



Certificate number: 62217/B0 BV

File number: .

Product code: 2202I

This certificate is not valid when presented without the full attached schedule composed of 7 sections

www.veristar.com

TYPE APPROVAL CERTIFICATE

This certificate is issued to

SAMSON REGULATION S.A.S.

VAULX EN VELIN CEDEX - FRANCE

for the type of product

GLOBE & ANGLE VALVES

GLOBE & ANGLE VALVES / Control valve type 3241

Requirements:

Bureau Veritas Rules for the Classification of Steel Ships

This certificate is issued to attest that Bureau Veritas Marine & Offshore did undertake the relevant approval procedures for the product identified above which was found to comply with the relevant requirements mentioned above.

This certificate will expire on: 22 Oct 2030

For Bureau Veritas Marine & Offshore,

At BV LYON, on 22 Oct 2025,

Michaël Vavro

This certificate was created electronically and is valid without signature



This certificate remains valid until the date stated above, unless cancelled or revoked, provided the conditions indicated in the subsequent page(s) are complied with and the product remains satisfactory in service. This certificate will not be valid if the applicant makes any changes or modifications to the approved product, which have not been notified to, and agreed in writing with Bureau Veritas Marine & Offshore. Should the specified regulations or standards be amended during the validity of this certificate, the product(s) is/are to be re-approved prior to it/they being placed on board vessels to which the amended regulations or standards apply. This certificate is issued within the scope of the General Conditions of Bureau Veritas Marine & Offshore available on the internet site www.veristar.com. Any Person not a party to the contract pursuant to which this document is delivered may not assert a claim against Bureau Veritas Marine & Offshore for any liability arising out of errors or omissions which may be contained in said document, or for errors of judgement, fault or negligence committed by personnel of the Society or of its Agents in establishment or issuance of this document, and in connection with any activities for which it may provide.

The electronic version is available at: <https://www.veristarm.com/veristarnb/jsp/viewPublicPdfTypepec.jsp?id=4hzo2zneoc>

BV Mod. Ad.E 530 June 2017

This certificate consists of 4 page(s)

THE SCHEDULE OF APPROVAL

1. PRODUCT DESCRIPTION

GLOBE & ANGLE VALVES / Control valve type 3241

1.1 - Ratings

Model	Type 3241
Size range (mm)	DN15-DN150 / NPS1/2 – NPS 6
Design Standard	ASME B16.34
Class range	Cl150-Cl300 PN10-PN16-PN25 PN40
Design Temperature (°C)	-50 / +400
End connections	Flange / Butt Welded

1.2 - Materials

Part	Material
Body	A216 WCC (1.0619) / A352 LCC (1.6220) / A182 F316 (1.4571) / A351 CF8M (1.4408) / A351 CF8 (1.4308) / A105 (1.0460) / A351 CF3M (1.4409)
Bonnet / Cover	A182 F316L (1.4404) / A216 WCC (1.0619) / A352 LCC (1.6220) / A182 F316 (1.4571) / A351 CF8M (1.4408) / A351 CF8 (1.4308) / A105 (1.0460) / A351 CF3M (1.4409)
Stem	1.4401/1.4404 - A479 316/A479 316L
Seat	1.4404 - A182 F316L
Plug	1.4401/1.4404 - A479 316/A479 316L or 1.4401/1.4404 - A182 316/A182 316L

When other choices of materials are used per manufacturer's recommendations, the BV agreement is to be obtained.

1.3 - Maximum Design Pressure in bar at ambient temperature (°C)

ANSI :

Material	CLASS150	CLASS300
A216 WCC / A352 LCC / A182 F316	19.8	51.7
A351 CF8M / A351 CF8	19	49.6
A105	19.6	51.1

DIN :

Material	PN10	PN16	PN25	PN40
1.0619 / 1.4408 / 1.6220 / 1.4308 / 1.0460 / 1.4571	10	16	25	40

2. DOCUMENTS AND DRAWINGS

- Drawing N°1129-0666 Rev.4 dated 29/04/2024 : Bill of material
- Drawing N°1010-5745-SWD Rev.2.b dated 16/02/2017 : Valve size 1/2" to 6"
- Drawing N° 1000119244 Rev.0 dated 19/09/2022 : Valve body size 3" - BWE
- Drawing N° 0102-4296 Rev.5 dated 13/11/2019 : Valve body size 1" - BWE
- Drawing N° 0102-7491 Rev.5.d dated 17/02/2012 : Valve body size 6" - BWE
- V/HE-1211-1 DE-EN dated 20/02/2014
- Mounting and operating instructions Edition July 2016
- T 8000-2 EN Edition January 2012
- T 8000-4 EN Edition January 2017
- Datasheet T 8012 EN Edition April 2018

No departure from the above documents shall be made without the prior consent of the Society. The manufacturer must inform the Society of any modification or changes to these documents and drawings.

3. TEST REPORTS

Not required.

4. APPLICATION / LIMITATION

4.1 - May be used for the following services on board:

- Shiplside valves - Sea water and fresh water - Bilge and ballast transfer - Compressed air - Cargo oil for tankers - Inert gas systems - Fuel-oil and lubricating oil transfer - Domestic and sanitary systems - Washing and fire extinguishing - Hydraulic oil - Deck foam systems - Non-essential systems

4.2 - The valves may be installed on systems of Class I, Class II and Class III according to the relevant requirements stated in *NR 467, Pt C, Ch 1, Sec 10*. Systems fitted on the ship side and collision bulkhead, and systems fitted on fuel oil and lub oil tanks under static pressure are of Class II.

4.3 - The valve body, plug and seat should be suitable for the intended service. In particular the nature of materials, joints included, is to be selected according to the fluid to be conveyed and the temperature.

4.4 - The approval does not include any operating gear for remote control of the valves.

4.5 - Bilge valves will be fitted in association with a non-return valve.

4.6 - The valves are to be installed according to the manufacturer's instructions and Society's Rule requirements.

4.7 - Reduction factors are to be taken in consideration for maximum working pressure caused by temperature influence according to manufacturer's instructions.

4.8 - Installation on board ships where a fire safe design is required remains to be approved on a case by case basis.

4.9 - The use of stainless steel and/or grey cast iron is restricted according to Bureau Veritas Rules *NR 467, Pt C, Ch 1, Sec 10, Table 5*.

5. PRODUCTION SURVEY REQUIREMENTS

5.1 - The products are to be supplied by **SAMSON REGULATION S.A.S.** in compliance with the type and the requirements described in this certificate.

5.2 - This type of product is within the category IBV of BV Rule Note *NR 320*.

5.3 - BV product certificate is required.

5.4 - BV Certificate is required for materials of valve housings of class I ($DN \geq 50$) or class II ($DN \geq 100$). Materials of valve housings of class I ($DN < 50$) or class II ($DN < 100$) and for other parts are to be with Work's certificates.

5.5 - Each valve housing for class I and class II is to be hydraulically pressure tested to 1.5 times the design pressure. Valves intended to be fitted on the shiplside below the load waterline are to be tested by hydraulic pressure not less than 0.5 MPa.

5.6 - For information, **SAMSON REGULATION S.A.S.** has declared to Bureau Veritas the following production site :

SAMSON REGULATION S.A.S.
1 RUE JEAN CORONA
BP 140
69512 VAULX EN VELIN CEDEX
FRANCE

6. MARKING OF PRODUCT

Each valve shall be permanently marked with at least:

- Manufacturer's name or logo
- Type designation
- Design Pressure and test pressure
- Bureau Veritas' Mark

7. OTHERS

It is **SAMSON REGULATION S.A.S.**'s responsibility to inform shipbuilders or their sub-contractors of the proper methods of fitting, use and general maintenance of the approved equipment and the conditions of this approval.

This certificate supersedes the Type Approval Certificates N° 62217/A1 BV issued by the Society.

***** END OF CERTIFICATE *****