

EU type examination certificate**EU-Baumusterprüfbescheinigung****CE-0085CQ0516**Product Identification No.
Produkt-Identnummer

Field of Application <i>Anwendungsbereich</i>	EU Gas Appliances Regulation (EU/2016/426) <i>EU-Gasgeräteverordnung (EU/2016/426)</i>
Owner of Certificate <i>Zertifikatinhaber</i>	Samson AG Weismüllerstraße 3, D-60314 Frankfurt am Main
Distributor <i>Vertreiber</i>	Samson AG Weismüllerstraße 3, D-60314 Frankfurt am Main
Product Category <i>Produktart</i>	accessories for gas appliances/pressure equipment: Automatic shut-off valve (4128)
Product Description <i>Produktbezeichnung</i>	2/2 way-valve with pneumatic actuator, current-free closed
Model <i>Modell</i>	3241G
Countries of Destination <i>Bestimmungsländer</i>	AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MT, NL, NO, PL, PT, RO, SE, SI, SK
Test Reports <i>Prüfberichte</i>	type testing: V-A 1560-01/18 from 10.01.2018 (TSG)
Test Basis <i>Prüfgrundlagen</i>	EU/2016/426 A III B (09.03.2016) DIN EN 16678 (01.02.2016) DIN EN 161 (01.04.2013)- partially DIN EN 13611 (01.12.2011)

Date of Expiry / File No. 26.02.2028 / 17-0750-GEA
Ablaufdatum / AZ

11.06.2018 Rie A-1/2

Date, Issued by, Sheet, Head of Certification Body
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle

DVGW CERT GmbH is an accredited body by DAkkS according to DIN EN ISO/IEC 17065:2013 and notified by the government of the Federal Republic of Germany for certification of gas appliances under EU Regulation

DVGW CERT GmbH ist von der DAkkS nach DIN EN ISO/IEC 17065:2013 akkreditierte und von der Deutschen Bundesregierung benannte Stelle für die Zertifizierung von Gasgeräten gemäß EU-Verordnung EU/2016/426.

Deutsche
Akkreditierungsstelle
D-ZE-16028-01-01DVGW CERT GmbH
ZertifizierungsstelleJosef-Wirmer-Str. 1-3
53123 BonnTel. +49 228 91 88 - 888
Fax +49 228 91 88 - 993www.dvgw-cert.com
info@dvgw-cert.com

Gas Category <i>Gasart</i>	Remarks <i>Bemerkungen</i>
fuel gases of the 1., 2. & 3. gas family	

Type <i>Typ</i>	Technical Data <i>Technische Daten</i>	Remarks <i>Bemerkungen</i>
3241-1-Gas; 3241-7-Gas	nominal diameter: DN 15	
3241-1-Gas; 3241-7-Gas	nominal diameter: DN 25	
3241-1-Gas; 3241-7-Gas	nominal diameter: DN 40	
3241-1-Gas; 3241-7-Gas	nominal diameter: DN 50	
3241-1-Gas; 3241-7-Gas	nominal diameter: DN 80	
3241-1-Gas; 3241-7-Gas	nominal diameter: DN 100	
3241-1-Gas; 3241-7-Gas	nominal diameter: DN 150	

Type Variation <i>Ausführungsvariante</i>	Explanations <i>Erläuterungen</i>
3241-1-Gas	with actuator type 3271
3241-7-Gas	with actuator type 3277

Hints of Utilization /Remarks

Verwendungshinweise / Bemerkungen

connection: flange connection according to DIN 2501 or ISO 7005 and optionally ANSI class 300

ambient temperature range: -40...+60 °C

class: D

max. operating pressure: 20 bar (seat diameter ≤ 48 mm), 15 bar (seat diameter 63 mm and 80 mm), 10 bar (seat diameter 100 mm), 5 bar (seat diameter 130 mm)