





CONFORMITY STATEMENT

(Translation)

- (2) Equipment and Protective Systems Intended for Use in Potentially Explosive Atmospheres **Directive 2014/34/EU**
- (3) Test Certificate Number:

PTB 03 ATEX 2016 X

Issue: 01

(4) Product:

(1)

e/p-positioner type 3730-28

(5) Manufacturer:

SAMSON AG Mess- und Regeltechnik

(6) Address:

Weismüllerstraße 3

60314 Frankfurt, Germany

- (7) This product and any acceptable variation thereto are specified in the schedule to this certificate and the documents therein referred to.
- (8) The Physikalisch-Technische Bundesanstalt, notified body No. 0102 in accordance with Article 17 of the Directive 2014/34/EU of the European Parliament and of the Council, dated 26 February 2014, certifies that this product has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of products intended for use in potentially explosive atmospheres, given in Annex II to the Directive.

The examination and test results are recorded in the confidential test report PTB Ex 16-25130.

(9) Compliance with the Essential Health and Safety Requirements has been assured by compliance with:

EN 60079-0:2012+A11:2013 EN 60079-15:2010 EN 60079-31:2014

- (10) If the sign "X" is placed after the certificate number, it indicates that the product is subject to special conditions for safe use specified in the schedule to this certificate.
- (11) This Conformity Statement relates only to the design and construction of the specified product in accordance with Directive 94/9/EC. Further requirements of this Directive apply to the manufacture and supply of this product.
- (12) The marking of the product shall include the following:

€x}

II 3 G Ex nA IIC T6 Gc and II 3 D Ex tc IIIC T80 °C Dc

Konformitätsbewertungsstelle, Sektor Explosionsschutz On behalf of PTB

Braunschweig, August 31, 2016

Dr.-Ing. F. Liene Regierungsdirek

Sheet 1/4





(13)

SCHEDULE

(14) CONFORMITY STATEMENT PTB 03 ATEX 2016 X, Ausgabe: 01

(15) Description of the product

The e/p-positioner type 3730-28 is a communication capable, single respectively double operating positioner for the attachment to all common lift or slewing-motion actuators. It is intended to assign the valve position to an actuating signal and it is a passive two-terminal network.

The attachment to pneumatic control valves respectively butterfly valves takes place either directly to the actuator of type series 3277 or by means of a NAMUR-adapter housing to conventional actuators.

Non-combustible media are used as a pneumatic auxiliary power.

In the future the e/p-positioner type 3730-28 may also be manufactured and operated according to the test documents listed in the test report.

The thermal and electrical maximum values are presented in the following.

For relationship between temperature class and permissible ranges of the ambient temperature, reference is made to the following table:

Gas- or dust group	Temperature class Permissible range of ambient temperature	
i i i i i i i i i i i i i i i i i i i	T6	-40 °C 60 °C
IIC	T5	-40 °C 70 °C
	T4	-40 °C 80 °C
IIIC	Not applicable	-40 °C 80 °C

Electrical data

Signal circuit (Terminals 11/12)	Nominal signal:	4 20 mA
Position indicator(Terminals 31/32)	Nominal signal:	4 20 mA
Sensor connection (Leakage-Sensor) (Terminals 31/32)	Capacitance	max. 1,4 nF
Binary input(Terminals 31/32)	Nominal signal:	6 30 V DC

Sheet 2/4





SCHEDULE TO EU-TYPE EXAMINATION CERTIFICATE PTB 03 ATEX 2016 X, Issue: 01

Changes:

The changes concern the update of the applied standards, cancelling of type of protection Intrinsic Safety, the application of alternative gasket material of the enclosure and the extension with an enclosure with a window.

No other technical changes were made to the equipment.

(16) Test report PTB Ex 16-25130

(17) Specific conditions of use

A fuse according to IEC 60127-2/II, 250 V F respectively IEC 60127-2/VI, 250 V T with a maximum nominal fuse current of $I_N \le 63$ mA shall be connected in series to the signal circuit (terminals 11/12).

The position indicator circuit (terminals 31/32) shall be connected to a fuse according to IEC 60127-2/VI, 250 V T with a maximum nominal fuse current of $I_N \le 40$ mA shall be connected in series. This fuse shall be arranged outside of the hazardous area.

A fuse according to IEC 60127-2/II, 250 V F respectively IEC 60127-2/VI, 250 V T with a maximum nominal fuse current of $I_N \leq 40$ mA shall be connected in series to the program interface adapter in the connection of Vcc.

The program interface adapter shall be arranged outside the hazardous area.

The connection of the wires has to be made in a way that the connection is free of tensile and torsional stress.

Sheet 3/4





SCHEDULE TO EU-TYPE EXAMINATION CERTIFICATE PTB 03 ATEX 2016 X, Issue: 01

(18) Essential health and safety requirements

Met by compliance with the aforementioned standards.

According to Article 41 of Directive 2014/34/EU, Conformity Statements which have been issued according to Directive 94/9/EC prior to the date of coming into force of Directive 2014/34/EU (April 20, 2016) may be considered as if they were issued already in compliance with Directive 2014/34/EU. By permission of the European Commission supplements to such Conformity Statements and new issues of such certificates may continue to hold the original certificate number issued before April 20, 2016.

Konformitätsbewertungsstelle, Sektor Explosionsschutz On behalf of PTB:

Braunschweig, August 31, 2016

Dr.-Ing. F. Liene Regierungsdirekt