Certificate of Conformity: IECEx PTB 08.0038X



IECEx Certificate of Conformity

INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification Scheme for Explosive Atmospheres for rules and details of the IECEx Scheme visit www.iecex.com				
Certificate No.:	IECEX PTB 08.0038X	issue No.:0	Certificate history:	
Status:	Current			
Date of Issue:	2008-08-26	Page 1 of 3		
Applicant:	SAMSON AG Mess- un Weismüllerstr. 3 60314 Frankfurt am Main Germany	ıd Regeltechnik		
Electrical Apparatus: Optional accessory:	Solenoid Valve Type 396	37-8		
Type of Protection:	Construction, test and n	narking of type of protection "	n" electrical apparatus;	
Marking:	Ex nA II T6 / Ex nL IIC T6 Ex tD A22 IP65 T 80 °C	3		
Approved for issue on be Certification Body:	ehalf of the IECEx	DrIng. Ulrich Johannsmeyer		
Position:		Department Head "Intrinsic Sa	fety and Safety of Systems"	
Signature: (for printed version)		Johany	, (
Date:		2008-08-28	>	
2 This certificate is not 1	chedule may only be reprodu transferable and remains the enticity of this certificate may	uced in full. e property of the issuing body. / be verified by visiting the Officia	I IECEx Website.	
Certificate issued by:	Taskaiseks Dundepende			
	Technische Bundesansta Bundesallee 100 38116 Braunschweig Germany	It (PTB)	PB	

Certificate of Conformity: IECEx PTB 08.0038X

		Certificate onformity	
Certificate No.:	IECEX PTB 08.0038X		
Date of Issue:	2008-08-26	Issue No.: 0	
		Page 2 of 3	
Aanufacturer:	SAMSON AG Mess- und Re Weismüllerstr. 3 60314 Frankfurt am Main Germany	geltechnik	
ound to comply with the I	s verification that a sample(s), representa EC Standard list below and that the manu was assessed and found to comply with	ative of production, was assessed and tested and ifacturer's quality system, relating to the Ex products the IECEx Quality system requirements. This scheme Rules, IECEx 02 and Operational	
documents, was found to	comply with the following standards:	ed in the schedule of this certificate and the identified	
IEC 60079-0 : 2007-10 Edition: 5 IEC 60079-15 : 2005-	Explosive atmospheres - Part 0:Equipment - General requirements Electrical apparatus for explosive gas atmospheres Part 15: Contruction, test and		
03 Edition: Ed 3	Marking of Type of Protection "n" electrical apparatus		
IEC 61241-0 : 2004 Edition: 1	Electrical apparatus for use in the pre requirements	paratus for use in the presence of combustible dust - Part 0: General s	
IEC 61241-1 : 2004 Edition: 1		lectrical apparatus for use in the presence of combustible dust - Part 1: Protection by	
This Certificate does n	ot indicate compliance with electrical safe expressly included in the Stand	ety and performance requirements other than those lards listed above.	
TEST & ASSESSMENT A sample(s) of the equip	REPORTS: ment listed has successfully met the exar	nination and test requirements as recorded in	
Test Report:			
DE/PTB/ExTR08.0046/0)		
Quality Assessment Rep DE/TUN/QAR06.0011/00			



IECEx Certificate of Conformity

Certificate No.: Date of Issue: IECEx PTB 08.0038X

2008-08-26

Issue No.: 0

Page 3 of 3

Schedule

EQUIPMENT:

Equipment and systems covered by this certificate are as follows:

The Model 3967-8.. Solenoid Valve converts electrical binary input signals into pneumatic output signals and serves for controlling pneumatic actuators. The device is intended for use inside of hazardous areas. For further information see annex

CONDITIONS OF CERTIFICATION: YES as shown below:

Conditions for safe use

- When the Model 3967-8... Solenoid Valve is to be used in hazardous locations where conductive dusts according to IEC 61241-1 are present, it shall be mounted in an additional enclosure of steel or stainless steel resp. or of plastic. Evidence shall be furnished that the enclosure inclusive of its connection facilities and bushings comply with Degree of Protection IP65 according to IEC 60529.

- When the Solenoid Valve is to be mounted in a plastic enclosure, the enclosure made by Manufacturer Rittal certified under PTB 03 ATEX 1011 U shall be used.

- Under normal operating conditions the input circuits provided with type of protection Ex nA II are permitted to be connected, disconnected or switched on/off while live only during installation, maintenance and repair work. The input circuits provided with type of protection Ex nL IIC are permitted to be switched on/off in normal operation.

Annexe: 3967-8_Technical Data.pdf